



J SERIES BOLLARDS

Solutions for vehicle access control
and city traffic

FAAC
Simply automatic.

RISING TO THE CHALLENGE OF VEHICLE ACCESS CONTROL

The J Series bollard represents a new generation access control solution. Many design innovations make it easy to handle and install but best of all its performance is market leading and lifetime costs exceptionally competitive. Activated by any access control system or signalling device, it is an alternative solution to fixed posts and barriers, allowing regulation of traffic into certain zones with high vehicle flow, (e.g. restricted areas, pedestrian areas, parking and industrial sites and many more). Available with a diameter of 275mm, and a height of 600mm or 800mm.

J 275 Bollard guarantees free pedestrian flow, but manages vehicle traffic or limited parking, with the following advantages:

- Does not disfigure the characteristics of the environment because of its mobile concealed element with minimal environmental impact
- Ensures greater protection of pedestrian areas in the town centre
- Allows access to authorised vehicles only
- Reduces and optimises the use of human resources in access control activities
- Customisable colour selection for blending in with the urban context
- Activity can be signalled by built-in buzzer and led outer ring, according to its position
- A full range of accessories is available
- Its function is to deter



TRULY INNOVATIVE AND UNIQUE BOLLARD

The J Series has a number of exceptional features.

The bollard was designed and tested in order to optimise installation, servicing and maintenance activities whilst maintaining maximum reliability over its lifetime.

1. New drive concept – the drive unit is mounted in the moving cylinder
2. High resistance steel structure
3. Fast moving cylinder
4. “Fully optional” version including all main accessories
5. Lowered maintenance costs, due to one man servicing.
6. Flexible control unit that manages up to 4 bollards
7. Possible replacement of first generation FAAC city bollards
8. Cylindrical shaped metal sheets make up the foundation box, enabling easy handling



12 REASONS TO EXPLAIN THE UNIQUENESS OF J 275 BOLLARD

- | | |
|----|--|
| 1 | Mobile drive unit, extractable by a handle for ease of replacement or maintenance |
| 2 | Cylinder slides on double rail to provide better stability in raising and lowering |
| 3 | No pipes with oil under pressure to avoid risk of failure's risks |
| 4 | Built-in illuminated outer ring powered by central led and acoustic buzzer |
| 5 | Built-in emergency release in case of power failure |
| 6 | Built-in mechanical release to lower the cylinder in any circumstances |
| 7 | Cylinder available in stainless steel AISI 316 |
| 8 | Internal fixing frames made of stainless steel |
| 9 | Connectors and junction boxes, with IP 67 certification |
| 10 | Round-section pit to optimize digging works |
| 11 | Pit supplied in a kit to minimise transport charges and packaging dimensions |
| 12 | JE 275 control board able to manage up to four bollards |

DIFFERENT VERSIONS APPLICATIONS

AUTOMATIC

Recommended for areas of daily frequent and necessary transits. Thanks to cards, remote controls or timer, the cylinder descends and rises automatically.

FIXED

Recommended to be combined where automatic bollards are present.



J 275H AUTOMATIC VERSION

TRAFFIC BOLLARD - **Hydraulic**

The J275 automatic concealed traffic bollard has fully integrated hydraulic technology for heavy duty usage. With a standard descent time of 2.8 seconds, there is an extra setting that activates the emergency release valve and allows a decent time of just 1 second. Even the basic bollard in the range comes with flashing lights, buzzer, emergency release and mechanical release.

AVAILABLE VERSIONS

PAINTED STEEL STANDARD VERSIONS

- **J 275/600 HA painted steel**
 - steel cylinder 7 mm thickness treated by cataphoresis and painted
 - powder painted dark grey metallised RAL 7021
 - Illuminated outer ring powered by central LED
 - buzzer
 - emergency release in case of power failure (failure safe or secure)
- **J 275/800 HA painted steel**
 - steel cylinder 7 mm thickness treated by cataphoresis and painted
 - powder painted dark grey metallised RAL 7021
 - Illuminated outer ring powered by central LED
 - buzzer
 - emergency release in case of power failure (failure safe or secure)

STAINLESS STEEL AISI 316 SPECIAL VERSIONS

- **J 275/600 HA satin finish stainless steel AISI 316**
 - stainless steel cylinder 6 mm thickness satin finished
 - Illuminated outer ring powered by central LED
 - buzzer
 - emergency release in case of power failure (failure safe or secure)
- **J 275/800 HA satin finish stainless steel AISI 316**
 - stainless steel cylinder 6 mm thickness satin finished
 - Illuminated outer ring powered by central LED
 - buzzer
 - emergency release in case of power failure (failure safe or secure)





| TECHNICAL SPECIFICATIONS | J 275/600 HA | J 275/800 HA |
|--|---|-----------------|
| Drive | Hydraulic | |
| Cylinder stroke | 600mm | 800 mm |
| Cylinder diameter | 275 mm | |
| Cylinder material standard release | Steel Fe360 | |
| Cylinder material special release stainless steel | AISI 316 | |
| Cylinder surface treatment | Cataphoresis and polyester powder painted dark grey metallised RAL 7021 | |
| Head surface treatment | Anticorodal case aluminium RAL 9006 | |
| Rising time | About 5,0 sec. | About 7 sec |
| Descent time (standard) | About 2,8 sec | About 3,5 sec |
| Descent time (rapid) (*) | 1 sec | 1,2 sec |
| Hydraulic drive unit | Power supply 230 Vac +6% - 10%; 50 Hz | |
| Power consumption | 220W | |
| Protection class | IP 67 | |
| Work frequency | Heavy duty | |
| Reflective strip | Standard height 55 mm | |
| Manual lowering operation | Simple hydraulic release key | |
| Impact resistance | 9.000 Joules | |
| Break in resistance | 120.000 Joules | |
| Walled in pit with cylinder profile | 560x560x950 mm | 560x560x1220 mm |
| Cable to link bollard to control unit (not supplied) | FG70R-0,6/1Kv-16G-1,5 | |
| Max cable length | 50 mt | |
| Environment temperature | -15 / +55°C | |

(*) By emergency release activation

ACCESSORIES FOR AUTOMATIC VERSION

- RAL paint on request (not available for satin finish stainless steel cylinder)
- Pit heater JH 275 (to extend operation up to -25°C)
- Pit cover JC 275
- Control unit JE 275 (up to max n. 4 bollards)
- Pit bollard JP 275/600
- Pit bollard JP 275/800.

TRAFFIC BOLLARD - Fixed

The fixed bollard is suitable for installations when all bollards don't need to be automated, the fixed bollards can maintain aesthetic appearances for sites, thus reducing costs and time of installation.

AVAILABLE VERSIONS

PAINTED STEEL STANDARD VERSIONS

- **J 275/600 F painted steel**
 - steel cylinder 4 mm thickness treated by cataphoresis and painted
 - powder painted dark grey metallised RAL 7021
- **J 275/800 F painted steel**
 - steel cylinder 4 mm thickness treated by cataphoresis and painted
 - powder painted dark grey metallised RAL 7021

STAINLESS STEEL AISI 316 SPECIAL VERSIONS

- **J 275/600 F satin finish stainless steel AISI 316**
 - stainless steel cylinder 3 mm thickness satin finished
- **J 275/800 F satin finish stainless steel AISI 316**
 - stainless steel cylinder 3 mm thickness satin finished





| TECHNICAL SPECIFICATIONS | J 275/600 F | J 275/800 F |
|---|--|-------------|
| Cylinder height | 600 mm | 800 mm |
| Cylinder diameter | 275 mm | |
| Cylinder material | Steel Fe 360 | |
| Cylinder material special release stainless steel | AISI 316 | |
| Cylinder surface treatment | Cataphoresis plus polyester powder painted dark grey metallised RAL 7021 | |
| Head surface treatment | Anticorodal case aluminium RAL 9006 | |
| Reflective strip | Standard height 55 mm | |

ACCESSORIES FOR FIXED VERSION

- Pit Bollard JPF 275.



HEADQUARTERS

ITALY

FAAC SpA
Via Calari 10 - 40069 Zola Predosa (BO)
Tel. +39 051 61724 - Fax +39 051 758518
info@faac.it - www.faac.it

SUBSIDIARIES

AUSTRALIA

FAAC AUSTRALIA PTY LTD
Homebush – Sydney, Australia
tel. +61 2 87565644
fax +61 2 87565677
www.faac.com.au

AUSTRIA

FAAC GMBH
Wals – Siezenheim, Austria
tel. +43 662 8533950
fax +43 662 85339520
www.faac.at

BENELUX

FAAC BENELUX NV/SA
Brugge, Belgium
tel. +32 50 320202
fax +32 50 320242
www.faacbenelux.com

CHINA

FAAC SHANGHAI
Shanghai, China
tel. +86 21 68182970
fax +86 21 68182968
www.faacgroup.cn

FRANCE

FAAC FRANCE
Corbas - Lyon, France
tel. +33 4 72218700
fax +33 4 72218701
www.faac.fr

FAAC NORD S.A.S.
Massy - Paris, France
tel. +33 1 69191620
fax +33 1 69191621
www.faac.fr

GERMANY

FAAC GMBH
Freilassing, Germany
tel. +49 8654 49810
fax +49 8654 498125
www.faac.de

INDIA

FAAC INDIA PVT. LTD
Noida – Delhi, India
tel. +91 120 3934100/4199
fax +91 120 4212132
www.faacindia.com

MIDDLE EAST

FAAC MIDDLE EAST BRANCH
Dubai Airport Free Zone - Dubai, UAE
tel. +971 42146733
fax +971 42146734
www.faac.ae

POLAND

FAAC POLSKA SP.ZO.O
Warszawa, Poland
tel. +48 22 8141422
fax +48 22 8142024
www.faac.pl

NORDIC REGIONS

FAAC NORDIC AB
BOX 125, SE-284 22
Perstorp, Sweden
tel. +46 435 779500
fax +46 435 779529
www.faac.se

SPAIN

F.A.A.C. SA
Alcobendas - Madrid, Spain
tel. +34 91 6613112
fax +34 91 6610050
www.faac.es

SWITZERLAND

FAAC AG
Altdorf, Switzerland
tel. +41 41 8713440
fax + 41 41 8713484
www.faac.ch

UNITED KINGDOM

FAAC UK LTD.
Basingstoke - Hampshire, UK
tel. +44 1256 318100
fax +44 1256 318101
www.faac.co.uk

U.S.A.

FAAC INTERNATIONAL INC
Jacksonville, FL - U.S.A.
tel. +1 904 4488952
fax +1 904 4488958
www.faacusa.com

FAAC INTERNATIONAL INC
Fullerton, California - U.S.A.
tel. +1 714 446 9800
fax +1 714 446 9898
www.faacusa.com

