

HEADQUARTERS

FAAC spa
Via Benini 1 40069 Zola Predosa (BO)
Tel. +39 051 61724 - Fax +39 051 758518
info@faac.it - www.faacgroup.com

FAAC SUBSIDIARIES

FAAC AG
Tel. +41 52 3461721
Fax +41 52 3461723
Illnau, Switzerland
www.faac.ch

FAAC FRANCE
Tel. +33 472218700
Fax +33 472218701
Corbas, France
www.faac.fr

FAAC GMBH
Tel. +49 8654 49810
Fax +49 8654 498125
Freilassing, Germany
www.faac.de

FAAC MIDDLE EAST
Dubai, Emirati Arabi
www.faac.ae
info@faac.ae

F.A.A.C. SA
Tel +34 91 6613112
Fax +34 91 6610050
Madrid, España
www.faac.es

FAAC UK LTD.
Tel. +44 1256 318100
Fax +44 1256 318101
Basingstoke Hampshire, UK
www.faac.co.uk

FAAC AUSTRALIA PTY LTD
Tel. +61 2 7565644
Fax +61 2 87565677
Homebush - Sydney, Australia
www.faac.com.au

FAAC NORD
Tel. +33 1 69191620
Fax +33 1 69536069
Massy, France
www.faac.fr

FAAC INDIA PVT. LTD
Tel. +91 120 3934100/4199
Fax +91 120 4212132
Noida - Delhi, India
www.faacindia.com

FAAC POLSKA SP.ZO.O.
Tel. +48 22 8141125
Fax +48 22 8142024
Warszawa, Polska
www.faac.pl

F.A.A.C. SA Delegación Cataluña
Tel. +34 93 4362000
Fax +34 93 5727994/4368225
Barcelona, España
www.faac.es

FAAC BENELUX
Tel. +32 50 320202
Fax +32 50 32024215
Brugge, Belgium
www.faac.be

FAAC GE.S. M.B.H.
Tel. +43 662 8533950
Fax +43 662 85339520
Wals - Siezenheim, Austria
www.faac.at

FAAC INTERNATIONAL INC.
Tel. +1 307 6351991
Fax +1 307 6328148
Cheyenne, USA
www.faacusa.com

FAAC SCANDINAVIA AB
Tel. +46 36 376860
Fax +46 36 370780
Bankeryd, Sweden
www.faac.se

FAAC SHANGHAI
Tel. +86 21 68182970
Fax +86 21 68182968
Shanghai, China
www.faac.com.cn

908475004 - Rev. 10 - 3.000 - Zucchini - 01/2009 The descriptions and illustrations contained in the present brochure are not binding. FAAC reserve the right to undertake product technical modifications without prior notice.



S418

Electro-mechanical 24V operator
for swing-leaf gates



A NEW OPERATOR FOR SWING-LEAF GATES: EASY TO INSTALL AND WITH A UNIQUE DESIGN

24V

- Long stroke + new multi-position attachments with fittings
- For single-leaf up to 2.7 m (2.3 m without electric lock)
- Integrated mechanical stops
- New control board with anti-crushing system and virtual encoder for inversion on obstacles
- Residential use.



EASY TO INSTALL:



Increased flexibility in the installation dimensions thanks to the 350 mm long stroke (390 mm without mechanical stops).



Suits a wide range of installations thanks to the multi-position attachments.

E 024/S Control board



E 124 Control board



Emergency kit XBAT 24V with NiMH batteries (not compatible with E 124)



TECHNICAL SPECIFICATIONS S418

Motor supply	24 Vdc	Type and frequency of use at 20°C	Residential use
Power	35 W	Operating ambient temperature	-20°C ÷ +55°C
Current	1,5 A	Weight	6 Kg
Thrust	180 daN	Dimensions (L x D x H)	825 x 104 x 125
Rod stroke	350 mm (390 mm without mechanical stops)	Protection class	IP44
Rod extension speed	1,8 cm/sec	Travel limit microswitches	NO
Leaf max length	2,7 m*	Opening and closing mechanical stops	YES

* Use of the electric lock is recommended over 2,3 m.